

ODORLESS PAINTERS SPIRITS - CAL. COMP.

TECHNICAL DATA SHEET

301



SUNNYSIDE ODORLESS PAINTERS SPIRITS CALIFORNIA COMPLIANT

DESCRIPTION

Sunnyside Odorless Painters Spirits California Compliant is an excellent choice for cleaning tar, grease and grime from car parts, lawn mowers, tools and machinery.

ITEM NUMBERS & SIZES

Pint	Quart	112 Oz.	2.5-Gal.	5-Gal.	55-Gal.
	30132	30188			

HAZARDOUS INGREDIENTS

Ingredient	CAS#	Percent
Petroleum Distillate	64742-47-8	100%

PHYSICAL PROPERTIES

Typical Properties	Results
GRAVITY, (60 °F)	
API	45.1
SPECIFIC	0.801
DENSITY (Lb./GAL)	6.67
DISTILLATION RANGE E, ° F.	430-520
FREEZING POINT, ° F (° C)	
KAURI BUTANOL (Kb) VALUE	
ANILINE POINT, °F	
FLASH POINT, T.C.C. °F	205
FLAMMABLE LIMITS IN AIR, % BY VOLUME	
LOWER, AT 100°F (38°C)	0.6
UPPER, AT 200°F (93°C)	5
AUTOIGNITION TEMPERATURE, °F (°C)	477°F
COLOR, SAYBOLT	+30
DOCTOR TEST	NEGATIVE
CORROSION, 3 HRS. @ 212 °F	1A
NON-VOLATILES, g/100ml	<0.0010
ACIDITY	NEUTRAL
ALKALINITY (AS NH ₃ , WT%)	
EVAPORATION RATE	Slower than ether
APPEARANCE	Clear, water-white
ODOR	Mild Petroleum Odor
VAPOR PRESSURE, mm Hg @ 20 °C	0.07
REFRACTIVE INDEX, @ 20 °C	
SULFUR CONTENT, PPM	<5
PURITY, by G.C., Wt%	
WATER CONTENT, Wt%	
WATER MISCIBILITY	Negligible
DOT SHIPPING NAME	
DOT CLASSIFICATION	
SHIPPING Wt. at 20 °C	6.67
V.O.C. (g/L)	4
(Cal. ARB definition)	

These properties are representative of typical inspections. They do not constitute product specifications. Consult MSDS sheet for additional information.

PRODUCT IMAGE**SAFETY INFORMATION**

HEALTH:	1
FIRE:	1
REACTIVITY:	0

PRODUCT APPLICATION

For degreasing, apply to a clean cloth and wipe thoroughly. For cleaning and degreasing large surfaces before painting: pour an appropriate amount of product into an empty paint can or other compatible container. Dip rag into container so that it becomes saturated; squeeze rag into container to remove excess product. Use wetted rag to wipe down surface. Repeat until surface is clean. Wipe surface dry prior to painting.

TEST METHOD

ASTM	Applied
D-278	■
D-1298	■
D-86	■
D-56	■
D-1255	■
D-156	■
D-484	■
D-130	■
D-1353	■
D-847	■
D-1614	■
D-1296	■
D-1218	■
D-1266	■
D-1364	■
D-1722	■

See MSDS sheet for additional Health, Safety, Handling and Regulatory Information available on our website at www.sunnysidecorp.com/msds.html