

SUNNYSIDE  
QUALITY PRODUCTS SINCE 1893

BACK TO NATURE

# READY-STRIP Graffiti Remover

Safely removes aerosol spray paints,  
varnishes, lacquers & more!

Removedor de graffiti

¡PRECAUCIÓN! IRRITA LOS OJOS Y LA PIEL.  
Lea las otras advertencias que aparecen en el envase.  
Usar sólo según las instrucciones.

32 FL.OZ. (946 ML)

CAUTION! EYE AND SKIN IRRITANT.  
Read other cautions elsewhere on container.  
Use only as directed.

Water Based  
Non-Flammable  
No Methylene Chloride  
Low VOC



For additional product information,  
visit [www.sunnysidecorp.com/  
graffitiremover](http://www.sunnysidecorp.com/graffitiremover)



For questions or comments about  
this product, call 1-800-323-8611  
or visit us on the web at  
[www.sunnysidecorp.com](http://www.sunnysidecorp.com)



Consumer Products Division  
Wheeling, IL 60090-6095

© 2014 S.C.

Ready-Strip Graffiti Remover™ is a safe, quick and easy way of removing unwanted aerosol paints, etc. from many surfaces without the use of harsh chemicals.  
**Removes:** Most varieties of aerosol paint, enamels, acrylics, oil and water-based paints, primers, semi-gloss and gloss paints, lacquers, and sealers. Effectively removes other graffiti type marks such as ink, crayon, magic marker, dyes, lipstick, shoe polish, etc.  
**Surfaces:** It works on most surfaces including brick, concrete, stone, cinder block, stucco, street signs, metal, steel, aluminum, vinyl and fiberglass. Also works on wood and plaster. Graffiti Remover is not to be used on sheetrock, plastic, rubber, linoleum, clothing or carpets. *On painted surfaces, care should be taken to remove the graffiti before the product penetrates the painted surface because it can soften paint. May strip latex painted surfaces.*

**TEST ALL SURFACES FOR POSSIBLE DAMAGE PRIOR TO USE. SHAKE BOTTLE BEFORE USE.**

**Application and Removal:** Mask any areas not being removed of graffiti with plastic and masking tape. Apply at temperatures between 60° and 80° F. Apply liberally to the surface. On vertical surfaces, apply as heavily as possible. Leave the stripper on approximately 1/2 hour to 1 hour. On non-porous surfaces, wipe the surface with a clean cloth or towel. On porous surfaces such as brick and concrete, use a stiff bristle or wire brush to loosen and agitate graffiti marks. Then scrape off, hose off with water, or use pressure washer with appropriate pressure to remove graffiti. After initial lifting, use a nylon brush or stripping pad with Ready-Strip Wash Wash or light amounts of water for final clean-up of residue. Repeat for tough, stubborn marks and stains. Clean up with water. Surface should be dry before applying any graffiti resistant coating.

**CAUTION:** CONTAINS BENZYL ALCOHOL, DIBASIC ESTERS AND FORMIC ACID. Do not transfer to unlabeled containers. May cause eye and skin irritation on contact.

**⚠ WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**SAFETY & FIRST AID:** Rubber gloves and safety glasses are recommended for eye and skin protection. Avoid eye contact. If eye contact occurs, immediately flush with plenty of water for 15 minutes. Avoid prolonged and repeated contact with skin. If skin contact occurs, wash with soap and water. Do not take internally. If swallowed do not induce vomiting. Give 1 or 2 glasses of water and call a physician immediately. Provide adequate ventilation in confined areas.

**KEEP OUT OF REACH OF CHILDREN.**

VOC 29.6% by weight