

M A T E R I A L S A F E T Y D A T A S H E E T

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Date of Prep: 9/4/2014

SECTION 1

SUNNYSIDE CORPORATION 225 CARPENTER AVENUE WHEELING, ILLINOIS 60090 EMERGENCY TELEPHONE	(847) 541-5700 (800) 424-9300	FOR INFORMATION: - SUNNYSIDE CORPORATION - CHEM TREC	(847) 541-5700
Product Class:	Mixture	Manufacturer's Code:	703
Trade Name:	M-1 Latex Paint Additive & Extender	NPCA HMIS:	Health: 1 Flammability: 0 Reactivity: 0

Product Appearance and Odor: Opaque liquid; mild odor.

SECTION 2 -- HAZARDOUS INGREDIENTS

OCCUPATIONAL EXPOSURE LIMITS

INGREDIENT	CAS #	PERCENT	ACGIH TLV (TWA)	ACGIH TLV (STEL)	OSHA PEL (TWA)	OSHA PEL (STEL)	VAPOR PRESSURE
Propylene Glycol	57-55-6	< 1%	Not Est.		Not Est.		0.1 MM Hg @ 70° F.

SECTION 3 -- EMERGENCY AND FIRST AID PROCEDURES

Inhalation:	Remove from exposure. Administer oxygen or artificial respiration as needed. Get medical attention.
Eye Contact:	Immediately flush with plenty of water for at least 20-30 minutes and get medical attention.
Skin Contact:	Remove contaminated clothing. Wash affected areas with soap and water. Obtain medical attention if irritation persists.
Ingestion:	DO NOT INDUCE VOMITING. Give 1-2 glasses of water to dilute. Get immediate medical attention.

SECTION 4 -- PHYSICAL DATA

The following data represent approximate or typical values. They do not constitute product specifications.

Boiling Range:	212 degrees (F) - I.B.P.	Vapor Density:	Heavier than air
Evaporation Rate:	Slower than ether	% Volatile By Volume:	99.7%
Weight Per Gallon:	8.32 lbs.		
Solubility in Water:	Complete		

SECTION 5 -- FIRE AND EXPLOSION DATA

Flammability Classification:	Non flammable
Flash Point:	NA
Auto ignition Temperature:	NA
Lower Explosive Limit:	NA
Extinguishing Media:	Water spray, dry chemical, CO2, alcohol foam.
Unusual Fire and Explosion Hazards:	Heat from fire can generate flammable vapor. Vapors can explode if confined. Vapors may travel long distances along ground before igniting and flashing back to ignition sources.
Special Fire Fighting Procedures:	Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Use water spray to keep fire-exposed containers cool.

SECTION 6 -- HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: Not Established.

EFFECTS OF OVEREXPOSURE

Inhalation: Irritation of nose, throat and eyes. Other possible symptoms of exposure include headache, nausea, narcosis, fatigue and loss of appetite.

Eye Contact: Irritating to the eyes and can cause pain tearing, reddening and swelling.

Skin Contact: Repeated or prolonged skin contact can result in dry, defatted and cracked skin causing increased susceptibility to infection.

Ingestion: Ingestion can result in irritation in the mouth., stomach tissue and digestive tract. Symptoms may include sore throat, abdominal pain, nausea, vomiting and diarrhea. Vomiting may result in chemical pneumonitis..

Chronic: No chronic health effects are expected form normal use. This material or its emissions may aggravate pre-existing eye disease.

Carcinogenicity: This product has not been identified as a carcinogen by NTP, IARC or OSHA.

Special Health Effects: This material or its emissions may aggravate pre-existing eye disease, asthma, respiratory disorders, skin allergies or eczema.

SECTION 7 -- REACTIVITY DATA

Stability: Stable

Conditions to Avoid: Heat, sparks, flame, strong oxidizing conditions.

Incompatibility (Materials to Avoid): Oxidizing materials can cause a reaction.

Hazardous Decomposition Products: Combustion produces carbon dioxide and carbon monoxide.

Hazardous Polymerization: Will not occur.

SECTION 8 -- SPILL OR LEAK PROCEDURES

Steps to be taken in case material is spilled or released: Remove ignition sources, evacuate area, avoid breathing vapor or contact with liquid. Recover free liquid or stop leak if possible. Dike large spills and use absorbent material for small spills. Keep spilled material out of sewers, ditches and bodies of water.

Waste disposal method: Incinerate under safe conditions; dispose of in accordance with local, state and federal regulations.

SECTION 9 -- SAFE HANDLING AND USE INFORMATION

Respiratory Protection: An appropriate NIOSH-approved respirator for organic vapor should be worn if needed.

Ventilation: General: Recommend at least ten air changes per hour for good general room ventilation.

Local Exhaust: If needed to control vapor below occupational exposure limits.

Protective Gloves: Solvent resistant.

Eye Protection: Chemical splash goggles and/or face shield must be worn when possibility exists for eye contact due to splashing or spraying liquid, airborne particles or vapor. Contact lenses should not be worn.

Other Protective Equipment: Safety shower, eye bath and washing facilities should be available.

Other Hygienic and Work Practices: Wash hands before eating, drinking, smoking, or using toilet facilities. Promptly remove soiled clothing/wash thoroughly before reuse. Shower after work using plenty of soap and water.

SECTION 10 -- SPECIAL PRECAUTIONS

Dept. of Labor Storage Category: Non flammable.

Hygienic Practices: Keep away from heat, sparks and open flame. Keep containers closed when not in use. Avoid eye contact. Avoid prolonged or repeated contact with skin. Wash skin with soap and water after contact.

Additional Precautions: Do not incinerate in closed containers.

Empty Container Warning: "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition. They may explode and cause injury or death. Do not attempt to clean since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged and promptly returned to supplier or disposed of in an environmentally safe manner and in accordance with governmental regulations.

SECTION 11 -- ADDITIONAL INFORMATION

This product contains the following toxic chemical(s) which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

TOXIC CHEMICAL	CAS #	APPROXIMATE % BY WEIGHT
NONE	NONE	NONE

SARA Title III Hazard Categories: None

Common Names: Paint Additive-Paint related Material

TRANSPORTATION* (U.S. D.O.T. land transportation in packages of 119 gallons or less)

Not regulated by US DOT as a hazardous material.

*Refer to CFR 49 for additional information/