



Product Number: 639

Product Name: 2-Minute Remover Gel

USE AND SAFETY INFORMATION

Directions: For your safety, read all information on this container before using. Use this product outdoors if possible. If used indoors, provide plenty of fresh air by opening all doors and windows to achieve cross ventilation. Do not use in basement or other unventilated areas.

Application: Open container carefully. Protect hands with solvent resistant gloves. Wear glasses or goggles to protect eyes. Apply a generous amount to area no larger than two feet by two feet at a time. Do not brush back and forth like paint. Allow the remover to stand undisturbed until the old finish softens enough to be removed with a putty knife. Use steel wool or a stiff brush for hard to get at places. Some finishes may require more than one application. To remove any remaining deep stain from wood, scrub with household bleach or oxalic acid solution and steel wool. Cool water and a scrub brush may be used for a final rinse. On fine wood and veneers use mineral spirits to prevent warping or raising the grain. Allow to dry thoroughly before refinishing. Rags and other waste should be allowed to completely air dry, and then disposed of in trash collection. For disposal guidance of unused product, contact a household hazardous waste program, or your local or state government environmental control agency.

Caution: This product can cause damage to most materials on contact. Avoid contact with all surfaces except those being worked on. Damages rubber, asphalt tile, plastic, fiberglass, and other synthetic materials. Product should be stored in a cool place, kept tightly capped and used within six months.

Limited Guarantee: When applied and used according to label directions, if not satisfied with this product, Sunnyside will refund your purchase price with proof of purchase at the company's option. This guarantee does not include labor, cost of labor for application or any related damages.

CAUTIONS: CONTAINS METHYLENE CHLORIDE, METHYL ALCOHOL, XYLENE, ETHYL BENZENE, DIPROPYLENE GLYCOL METHYL ETHER & PETROLEUM DISTILLATE. Cannot be made non-poisonous. Keep away from heat and flame. Contact with flames or hot surfaces can produce toxic gases. DO NOT smoke. Vapor harmful. Do not allow vapors to accumulate. Avoid contact with skin or eyes. Open container slowly to relieve pressure and close after each use. Do not transfer to unlabeled containers.

Health Note: Contains Methylene Chloride which has been shown to cause cancer in certain laboratory animals. Possible risk to your health depends on level and duration of exposure.

Other Health Hazards: If during use you experience discomfort such as eye watering, headache or dizziness, increase fresh air or leave the area. The use of a respirator is not recommended unless professionally supervised. Dust masks provide no protection from vapors. Persons with heart or respiratory problems should avoid use of this product. Exposure to Methylene Chloride, a component of this product, REDUCES THE BLOOD'S OXYGEN CARRYING CAPACITY. Reports have associated repeated or prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal. May be harmful if absorbed through the skin.

WARNING: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

First Aid: If swallowed, DO NOT induce vomiting. GET IMMEDIATE MEDICAL ATTENTION! Call physician, hospital emergency room or poison control center immediately. In case of eye or skin contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Get medical attention. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention.

Use only with adequate ventilation.

KEEP OUT OF REACH OF CHILDREN.

California SCAQMD Rule 443.1: Max. VOC: 181 g/L; Max. Vapor Pressure: Non-Exempt VOC: 100 mm Hg; Exempt VOC: 350 mm Hg; Non-photochemically Reactive. Less than 50% VOC.