



Product Number: 663

Product Name: Ready-Strip Safer Paint Remover

USE AND SAFETY INFORMATION

Ready-Strip Spray is not to be used on sheetrock, plastic, rubber or linoleum surfaces.

DO A TEST AREA FIRST TO DETERMINE RESULTS. SHAKE BOTTLE BEFORE USE.

Directions: Mask any areas not being stripped with plastic and masking tape. Apply at temperatures between 60° and 80° F. Apply Ready-Strip-Spray liberally to the surface. On vertical surfaces, apply as heavily as possible. Depending upon the type and amount of paint, the remover can work in as little as 30 minutes, or stay wet and active for up to 4 hours or more. Periodically test scrape a small area to determine if the paint or varnish is ready to be removed. Use a stiff putty knife to lift paint from flat surfaces or a stiff bristle brush for detailed areas. After initial lifting, use a nylon brush or stripping pad with After-Strip Paint Remover Wash or light amounts of water for final clean-up of residue. Clean up with water. Surface should be dry before repainting.

CAUTIONS: CONTAINS N-METHYL-2-PYRROLIDONE AND DIBASIC ESTERS. Do not transfer to unlabeled containers. May cause eye and skin irritation on contact.

WARNING: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

SAFETY & FIRST AID: Rubber gloves and safety glasses are recommended for eye and skin protection. Avoid eye contact. If eye contact occurs, immediately flush with plenty of water for 15 minutes. Avoid prolonged and repeated contact with skin. If skin contact occurs, wash with soap and water. Do not take internally. If swallowed, do not induce vomiting. Give 1 or 2 glasses of water and call a physician immediately. Provide adequate ventilation in confined areas.

KEEP OUT OF REACH OF CHILDREN.

California SCAQMD Rule 443.1:Max. VOC 491 g/L; Max Vapor Pressure of VOC: 0.3 mm Hg. Non-photochemically Reactive. Less than 50% VOC.