



Product Number: 678

Product Name: Ready-Strip Heavy Duty Adhesive Remover

USE AND SAFETY INFORMATION

- **READY-STRIP ADHESIVE REMOVER™** will safely remove most mastics and adhesives in a single application.
- Stays wet for extended periods of time to penetrate and lift heavy builds.
- User Friendly • Odorless • Heavy Duty • Non-Flammable • Safer to Use • Easily Cleaned-Up with Water
- Contains NO Methylene Chloride or caustics.
- No drip formula clings to vertical surfaces and completely fills detailed areas.
- Use on interior or exterior surfaces including wood, plaster, concrete, brick, stone, masonry, marble, metal and veneers (DO NOT use on sheetrock, plastic, rubber or linoleum surfaces)
- Works on most Construction Adhesives, Flooring Adhesives, and Contact Cement.
- **Stir only. DO NOT SHAKE.**

Directions: Mask any areas not being removed with plastic and masking tape. For best results apply at temperatures between 60°F and 80°F. Apply READY-STRIP™ ADHESIVE REMOVER liberally to the surface with a brush, 1/2" nap paint roller, putty knife, or squeegee so that the remover completely covers the color of the surface to be stripped (20 mils thick). **Do not brush out too thin like a coat of paint.** It covers approximately 35-50 sq. ft. per half gallon. Check applied area at 2-4 hours, then periodically thereafter. As a rule of thumb, the thicker the mastic, the longer the product should be left on. The remover will usually remove most mastics and adhesives within 6-8 hours. Heavier builds may take longer (12-24+ hours). Use a stiff putty knife or floor scraper to lift the mastic or adhesive. After initial lifting, use a nylon brush or stripping pad with READY-STRIP™ Wash or light amounts of water to remove any residue. Final clean-up should be done with water. No need to neutralize (acid wash) surface. Surface should be completely dry before application of new mastic or adhesive. Clean tools promptly after use with soap and water.

Hints: Let the **READY-STRIP ADHESIVE REMOVER** do the work. Give it the proper time to penetrate the adhesive layers or its purpose is defeated. Misting the area to be removed with water prior to removal may make lifting of the coating easier. If desired results are not achieved at first, leave remover on longer if still wet, or apply a thicker coat. If still tacky and moist, reapply remover over itself. If completely dry, scrape off and reapply. Product activity is reduced below a temp. of 60°F and may require additional dwell time before all layers of adhesive are removed.

CAUTIONS: CONTAINS N-METHYL-2-PYRROLIDONE, DIBASIC ESTERS, AND FORMIC ACID. Do not transfer to unlabeled containers. May cause eye and skin irritation on contact. Close container after use.

WARNING: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

SAFETY & FIRST AID: Rubber gloves and safety glasses are recommended for eye and skin protection. Avoid eye contact. If eye contact occurs, immediately flush with plenty of water for 15 minutes. Avoid prolonged and repeated contact with skin. If skin contact occurs, wash with soap and water. Do not take internally. If swallowed do not induce vomiting. Give 1 or 2 glasses of water and call a physician immediately. Provide adequate ventilation in confined areas or use NIOSH approved respirator.

KEEP OUT OF REACH OF CHILDREN.

California SCAQMD Rule 443.1:Max. VOC 226 g/L; Max Vapor Pressure of VOC: 28.5 mm Hg. Non-photochemically Reactive. Less than 20% VOC.