

Product Number: 725

Product Name: Wood Protectant

## USE AND SAFETY INFORMATION

**Surface Preparation:** All surfaces must be clean and free of mold, mildew and any previous finishes. Check for porosity by applying a few drops of water. If the water is quickly absorbed, the surface is ready for application. To check for acceptable appearance, always apply to a small test area and allow to dry prior to coating larger areas.

**Application:** Shake container before using. Apply a generous coat with a low pressure sprayer, synthetic brush or roller. Apply a uniform coat, avoid pooling or drips. This product should fully penetrate into surface within 10 minutes. Single coat application is recommended. Re-apply every 1-2 years, depending on exposure. Recently treated surfaces may be slippery until dry and weathered. Coverage 100-250 sq. ft./gallon depending on surface. Dries clear in one hour. Complete drying depends on temperature, humidity and porosity of surface.

**Cleanup and Disposal**: Cleanup brushes and equipment with soap and water. Dispose of unused material in accordance with local, state and federal regulations. Close container after each use.

**Protect from Freezing:** Do not apply at temperatures below 40° F. during application and drying. Do not apply to painted or sealed surfaces. Do not thin or mix with other products.

**CAUTION:** May be harmful if swallowed. Avoid breathing vapors or spray mist. May be irritating to eyes and skin. Use goggles and protective clothing to avoid exposure. If you experience eye watering, headaches or dizziness, increase fresh air or leave the area. Keep container closed when not in use. Do not transfer to unlabeled containers.

**Health Hazards:** Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Avoid breathing vapor or spray mist. If you experience eye watering, headaches, dizziness or have difficulty breathing, increase fresh air or wear respiratory protection (NIOSH approved) or leave the area to obtain fresh air. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. May be harmful if absorbed through the skin.

**Limited Guarantee:** When applied according to label directions, if you are not satisfied with this product Sunnyside will refund your purchase price with proof of purchase at the company's option. This guarantee does not include labor, cost of labor for application or any related damages.

WARNING: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

**First Aid:** If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush thoroughly with water for 15 minutes and then get medical attention; for skin contact, wash thoroughly and get medical attention if irritation persists.

Use only with adequate ventilation.

## KEEP OUT OF REACH OF CHILDREN.

California SCAQMD Rule 443.1: Less than 20 g/L VOC; Max. Vapor Pressure of VOC: 17mm Hg @ 20°C; Non-photochemically Reactive.